

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	Somas Instrument AB
Address	Norrlandsvägen 26-28, 661 40 Säffle, Sweden
Place of Production	Somas Instrument AB P.O. Box 107, SE-661 23 Säffle, Sweden
Type	Butterfly Valves
Description	High temperature wafer type butterfly valve, metal seated
Trade Name	SOMAS butterfly valves
Application	Marine, offshore and industrial use subject to the following marine exclusions: <ul style="list-style-type: none">• Shipline valves.• Compressed air or gas systems having a pressure greater than 7 bar.• As outlet valves on compressed air receivers.• As terminal valves or deep tank outlet valves in flammable fluid systems inside machinery spaces or other spaces where a source of ignition is present.
Specified Standard	Lloyd's Register's Rules and Regulations for the Classification of Ships; ANSI B16.104
Ratings	Nominal diameter (mm): 80, 100, 125, 150, 200, 250, 300, 350, 400, 450, 500, 600, 700 & 800 Max-working pressure (bar): 25 Max-working temperature (°C): 550

71 Fenchurch Street, London, EC3M 4BS, UK

M.H.M.Rila

Senior Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

Other Conditions

1. Valves are to be selected, installed and tested in accordance with the manufacturer's recommendations and LR's Rules and Regulations for the Classification of Ships, Part 5, Chapter 12.
2. Material impact test and wed-non-destructive tests are to be carried out in accordance with the LR Rules for Materials.
3. Due care should be taken not to over stress the fittings when tightening the bolts.
4. The valves are to be marked with the following information:
 - Manufacturer's name or trademark
 - Pressure rating
 - Temperature range
 - Size

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

The Design Appraisal Document No. LR2002533TA and its supplementary Type Approval Terms and Conditions form part of this Certificate.